



EUROCEL MSK 80

Short description:

Masking tape for automotive repair workshops

Product Data

Backing:	59 g/m ² yellow saturated crepe paper
Adhesive:	natural rubber and resins solvent based
Total thickness	0.125 mm
Adhesion to steel	5.4 N/25mm
Tensile strength MD	87.5 N/25mm
Elongation at break	9 %
Temp. Resistance	110 °C (30 min), suitable for 80°C oven drying

Application

Masking tape suitable for applications requiring high temperature resistance

Features	Benefits
Natural rubber and resins solvent based adhesive	<ul style="list-style-type: none">➤ Good adhesion even on irregular surfaces➤ High performance even in overlapping and with masking paper applied➤ Heat resistant up to 110°C (30 minutes)➤ Usable even for refinishing with Infra Red lamps➤ Resistant to paint and lacquer thinners➤ Easy removal without adhesive residue
Saturated paper backing	<ul style="list-style-type: none">➤ The yellow colour allows even shading, creating clear contrast with most frequent colours➤ Well adaptable to most shapes➤ Compatible with most common paints and lacquers➤ Removable without breaking➤ Hand tearable

Product shelf life and storage: 12 months, based on the product being stored at 23°C/50% relative humidity out of direct sunlight.